404 DU0

Vimek 404 DUO unites the best of both worlds. It combines a harvester and a forwarder in one machine.



Powerful and fuel efficient CAT engine

Dual control

with market's sharpest swing angle

DASA Forester Bucking system
H50 or H70

Keto Forst Xtreme (option)

Harvesting unit with improved functions

Powerful hydrostatic with different drive modes

Disconnectable wheel drive enables transportation on a dolly trailer



Equipment

Standard

Air conditioning

Medium LED lightning

Radio with Bluetooth

Options

Pneumatic chair

Sprinkler system

Filling pump hydraulic oil

Refueling pump diesel

Diesel engine heater

Callstart till Diesel engine heater

Crane damping system

Sun blinds

Large LED lightning

Stump treatment system

PC with rear camera

Rear camera

Tool holder

Ball hitch

Accessories

Clam shell bucket

Boggie tracks, trailer

Wheel chains 500/60-22.5 or 405/70-24

Computer caliper

Vimek C12 thinning head

Transport and tool replacement kit

Chainsaw holder

Dolly trailer



404 DU0

Technical specifications

Engine

CAT C2.2T CRDI 50 kW

Swing angle

80

Transmission

Hydrostatic / mechanical

Tyres

405/70-24 or 500/60-22.5

Hydraulic 120 L/min

l - - .. - . - - -

Ground clearence

40 cm

Wheelbase

2.10 m

<u>Lenght</u>

4.65 m

9.25 m including trailer

Width

1.80 m or 2.05 m

Weight

4,700 kg, trailer excluded

Loading area

Loading area 3.40 m with cargo space 2.00 m²

Loading capacity

5,500 kg

<u>Crane</u>

Vimek – Mowi P25

Range: 5.2 m

Lifting capacity: 400 kg at 5.2 m

Gripping area: 0.16 m²

Harvesting unit

Keto Forst Supreme V3

Weight: 296 kg

Max. diameter: 300 mm

10 cc saw engine

Keto Forst Xtreme (option)

Weight: 300 kg

Max. diameter: 300 mm

10 cc saw engine

Bucking system

DASA H50/H70

